

INSTALLATION INSTRUCTIONS

FM0406

SAFETY PRECAUTIONS:

Read all safety precautions and installation instructions carefully before installing or servicing this fixture. Failure to comply with these instructions could result in potentially fatal electric shock and/or property damage.

It is recommended that all wiring be performed by a qualified electrician. This fixture must be wired in accordance with all national and local electrical codes.

Do not handle any energized fixture or attempt to energize any fixture with wet hands or while standing on a wet or damp surface or in water.

Make sure that the power source conforms to the requirements of the fixture (see labels on fixture housing).

To reduce the risk of electrical shock, and to assure proper operation, this fixture must be adequately grounded. To accomplish proper grounding, there must be a separate ground wire (green) or bare metal contact (metal conduit) between this fixture and the ground connection of your main power supply panel.

INSTALLATION INSTRUCTIONS

1. PREPARING FOR INSTALLATION

A. Carefully remove the fixture from the carton, and check that all parts are included, as shown in figure.

B. Tools and material needed: screwdriver, pliers, wire nuts, electrical tape.

C. To help prevent the possibility of electrical shock, the use of rubber sole shoes is recommended.

D. Exercise care when handling the fixture to avoid cuts or abrasions.

E. Disconnect electrical power at fuse or circuit breaker box before installing or servicing any part of this fixture.

F. Separate mounting bracket from fixture housing by counterclockwise twisting fixture housing.

2. MOUNTING & WIRING

(all wiring must take place inside junction box)

A. Electrical connection: Make sure electricity to the circuit is turned off. Connect green/or bare copper wire to Ground screw (Ground must be properly installed or unit may not work). Connect white wire to white supply wire cover with nut/or twist together and cover really well with electrical tape. Connect black wire supply wire cover with a wire nut/or twist together and cover really well with the electrical tape.

B. Install mounting bracket to junction box (not provided) by tighten two mounting screws to secure it.

C. Adjust CCT switch on the back of the fixture according to the desired color temperature as shown below.
Note: Fixture is preset to 3000K from factory.

D. Align the top of fixture housing and mounting bracket then clockwise twist fixture housing to hold secure mounting bracket.

E. Turn power on.

